

TEKLITE TUBIE 285 INSTRUCTIONS





PLEASE COMPLETELY UNDERSTAND ALL USER INSTRUCTIONS AND SAFETY INFORMATION BEFORE USING THIS PRODUCT. AS WITH ANY HIGH TECH PRODUCT You will need to routinely check for loose hardware, cracks or other damage and replace items as necessary. Do not use product if any of these conditions exist.

TEKUTE TUBIE 285 INSTALLATION INSTRUCTIONS:

STRAPS AND HARDWARE INCLUDED

- a. Frame straps, 189 x 19 mm (x2)
- b. M5 x 16 mm button flange bolts (x2)



TOOLS REQUIRED 4 mm Hex Wrench Torque Wrench 1.1 Nm



A. MOUNTING BAG USING STRAPS

With the Velcro facing towards the bag, feed the round end of a frame strap through one of the slots on the bottom of the bag. Repeat with the second frame strap. **Figure A**.

Position the bag on whatever main frame tube or seatpost that will be safe, and where the bag will not interfere with any rotating or moving part of the bike. Wrap the strap around the tube and thread the end through the buckle. Pull the strap tight and push the hook end of the Velcro into the soft loop surface of the strap ensuring a secure fasten. Repeat with second strap. **Figures B & C.**





Figure B



Top tube bag installation using straps **Figure C**

TEKLITE TUBIE 285 INSTRUCTIONS

B. MOUNTING BAG USING BOLTS

Insert the M5 x 16 mm flange bolts through the slits and holes until they protrude through the bottom of the bag. Locate which set of threaded inserts you will be using to mount the bag. Using a 4 mm Hex wrench, torque each bolt to 1.1 Nm (10 lbf-in). Figure D & E.





Figure D

Bolt-mounting on downtube

Figure E

VERSATILE MOUNTING OPTIONS

You can mount the Tubie 285 virtually anywhere! Place on top tube, seat post, downtube...you can even mount it upside down!



CARE INSTRUCTIONS:

- Hand wash with warm water and dish soap to prolong life of bag.
- Do not use bleach or cleaners containing chlorine.
- Clean zipper and zipper garage with a toothbrush, regularly.
- Air dry

WARRANTY:

Materials and workmanship have a limited warranty of 5 years. Normal wear and tear is excluded.

DAWNTODUSK.BIKE